

SUMO - More on... Software Tests

Daniel Krajzewicz

Danilot Tete Boyom

SUMO - More on... Software Tests

Daniel Krajzewicz

Danilot Tete Boyom

\$Revision: 3772 \$

Table of Contents

1. Introduction	1
Document Information	1
Document Scope	1
Document Audience	1
Document Structure	1
2. Acceptance Testing using TextTest	2
About	2
Install	2
Running the Tests	2
Setting up new Tests	2
Coverage	2
DFROUTER	3
DUAROUTER	4
JTRROUTER	5
NETCONVERT	6
SUMO	8

List of Tables

2.1. Tests for DFROUTER	3
2.2. Tests for DUAROUTER	4
2.3. Tests for JTRROUTER	5
2.4. Tests for NETCONVERT	6
2.5. Tests for SUMO	8

Chapter 1. Introduction

Document Information

This document is a part of *SUMO* - Simulation of Urban *MO*bility. SUMO is an open source microscopic road traffic simulation. It can be found under <http://sumo.sourceforge.net/>.

This document fits to version 0.9.5. We will try to keep it up-to-date with the next versions.

Document Scope

Since version 0.9.3 we support some basic tests which prove the software functionality. The number of the available tests is not that large, yet, but it will hopefully grow with time. This chapter describes how to set up the testing system and how to use it.

Document Audience

This document contains information for *developers* who extend SUMO and want to assure their changes work properly.

Document Structure

At first, the acceptance tests that come with the package are described.

Chapter 2. Acceptance Testing using TextTest

About

We use "TextTest [<http://texttest.carmen.se/>]" to test whether the software still behaves as expected. What this application does is simply to compare an application's output (both normal and errors) and optionally also the files written by the application with previously generated files.

There are some advantages and disadvantages of this approach. On the one hand, you can guarantee that the application is doing what is wanted by comparing all outputs with files you think are right. But this is also the problem with this approach: you do not have the assurance that the files you are comparing the current outputs to ARE right - you have to check these by hand.

Anyhow, for the current progress stage, this approach should be used, because a) the tests are quite small and errors can be easily seen b) it is working.

Install

At first, you have to download and install "TextTest [<http://texttest.carmen.se/>]" from <http://texttest.carmen.se/>. The installation seems to be not that easy at first, but if you just follow the steps described in TextTest's documentation, you'll have the system up and running in some minutes. Before continuing, please check whether the tests included with the TextTest distribution run before proceeding.

After installing TextTest, you have to set an environment variables in order to make the system run:

- TEXTTEST_HOME

Set it to the path SUMO-tests are located in (`<SUMO_DIST>/tests` for the tests that come with the distribution)

This environment variable forces TextTest to use the specified directory as source of tests.

This should be all on installing the tests-subsystem so far...

Running the Tests

Within the `<SUMO>/tests` - folder you can find batch-files which start TextTest. "runAllTests.bat" starts TextTest for testing all applications located in the folder, "runNetconvertTests.bat" will only show tests for NETCONVERT, "runDuarouterTests.bat" only those for DUAROUTER etc.

Setting up new Tests

Please follow the instructions for TextTest. In the following, the TextTest configuration for each application will be discussed.

Coverage

As said before, further tests have to be added. The following tests are currently available:

DFROUTER

Table 2.1. Tests for DFROUTER

Test Set Description	
<i>Tests whether showing meta-information works</i>	
Path	Description
dfrouter/meta/help	checks whether printing help works
dfrouter/trips/noop	checks what happens when no argument is given
<i>Checks whether the detector types are computed properly</i>	
Path	Description
dfrouter/detector_types/ messstrecke	Example using the dlr-testtrack
<i>Checks whether the detector pois are written correctly</i>	
Path	Description
dfrouter/detector_pois/ messstrecke	Example using the dlr-testtrack
<i>Checks whether the routes are computed correctly</i>	
Path	Description
dfrouter/routes/messstrecke	Example using the dlr-testtrack
<i>Checks whether error handling works</i>	
Path	Description
dfrouter/errors/false_net	Tests what happens if an unknown network is passed
dfrouter/errors/no_output	Tests what happens if no output is given
dfrouter/errors/unknown_option	Tests what happens if an unknown option is passed

Recent changes:

- Test for `--version` was removed in version 0.9.5

DUAROUTER

	duarouter/trips/increasing_time_typedefined_withcolor	same as increasing_time_typedefined, but the type is given and defined in the trips
	duarouter/trips/increasing_time_unsorted	same as increasing_time, but with - -unsorted set
	duarouter/trips/increasing_time_withcolor	same as increasing_time, a color is given partially
	duarouter/trips/one_time	100 trips, one departure time
	duarouter/trips/one_time_notype	same as increasing_time, but no type is given in the trips
	duarouter/trips/one_time_typedefined	same as increasing_time, but a type is given and defined in the trips
	duarouter/trips/one_time_unsorted	the same, but with - -unsorted set
	duarouter/trips/unsorted_time	100 trips, random departure time, - -unsorted set
	duarouter/trips/unsorted_time_notype	same as unsorted_time, but no type is given in the trips
	duarouter/trips/unsorted_time_typedefined	same as unsorted_time, , but a type is given and defined in the trips
	Checks whether the import of routes (SUMO) works	
	Path	Description
	duarouter/routes/increasing_time	100 routes (old style), departure time is increasing
	duarouter/routes/one_time	100 routes (old style), one departure time
	duarouter/routes/unsorted_time	100 routes (old style), random departure time, - -unsorted set
	duarouter/routes/newstyle_withid_increasing_time	100 routes (new style, routes have an id), departure time is increasing
	duarouter/routes/newstyle_withid_one_time	100 routes (new style, routes have an id), one departure time
	duarouter/routes/newstyle_withid_unsorted_time	100 routes (new style, routes have an id), random departure time, - -unsorted set
	duarouter/routes/newstyle_noid_increasing_time	100 routes (new style, routes have no id), departure time is increasing
	duarouter/routes/newstyle_noid_one_time	100 routes (new style, routes have no id), one departure time
	duarouter/routes/newstyle_noid_increasing_time	100 routes (new style, routes have no id), increasing departure time
	duarouter/routes/newstyle_noid_unsorted_time	100 routes (new style, routes have no id), random departure time, - -unsorted set
	duarouter/routes/newstyle_increasing_colors	same as newstyle_noid_increasing_time, but colors are supplied partially
	duarouter/routes/newstyle_with_vehtype	Another (!!!) color check
	duarouter/routes/newstyle_with_vehtype	newstyle_withid_one_time, but the with a defined vehicle type
	duarouter/routes/newstyle_with_vehtype_nodef	newstyle_withid_one_time, but the with an undefined vehicle type
	duarouter/routes/newstyle_with_vehtype_withclass	newstyle_with_vehtype, but the vehicle type has a class
	Checks whether the DUA works	
	Recent changes:	
	Path	Description
	duarouter/dua/newstyle_dua3s_step1	the first step of the dua3s-example using current (new style) output; converts trips to routes and alternatives
	duarouter/dua/newstyle_dua3s_step2	the second step of the dua3s-example using current (new style) output; converts alternatives

- Test for `--version` was removed in version 0.9.5

JTRROUTER

Table 2.3. Tests for JTRROUTER

Test Set Description	
<i>Tests whether showing meta-information works</i>	
Path	Description
dfrouter/meta/help	checks whether printing help works
dfrouter/trips/noop	checks what happens when no argument is given
<i>Checks plain functioning</i>	
Path	Description
dfrouter/plain/plain	A basic test
dfrouter/plain/no_turnarounds	As plain, but turning around is prohibited (by setting the probability to zero)
dfrouter/plain/straight_only	As plain, but only moving forward is allowed (by setting all other probabilities to 0)
dfrouter/plain/straight_only	As straight_only, but the ending edge is a sink
<i>Checks whether the processing of turn definitions works</i>	
Path	Description
dfrouter/turns/definite_xml	Description of two routes using turn definitions in XML
dfrouter/turns/definite_csv	Description of two routes using turn definitions in CSV
<i>Checks whether error handling works</i>	
Path	Description
dfrouter/errors/no_net	Tests what happens if the net is not given
dfrouter/errors/false_net	Tests what happens if the net is not available
dfrouter/errors/no_output	Tests what happens if the output is not given
dfrouter/errors/false_output	Tests what happens if the output can not be written
dfrouter/errors/no_input	Tests what happens if the input is not given
dfrouter/errors/unknown_option	Tests what happens if an unknown option is passed

Recent changes:

- Test for `--version` was removed in version 0.9.5

NETCONVERT

Path	Description
netconvert/meta/help	checks whether printing help works
netconvert/trips/noop	checks what happens when no argument is given
Checks whether --speed-in-kmh works (in XML)	
Path	Description
netconvert/XML2/speed_in_kmh/cross_notypes_kmh	no types, speed in kmh
netconvert/XML2/speed_in_kmh/cross_notypes_kmh_v	the same, with verbose output
netconvert/XML2/speed_in_kmh/cross_usingtypes_kmh	types, speed in kmh
netconvert/XML2/speed_in_kmh/cross_usingtypes_kmh_v	the same, with verbose output
Checks whether types may be used to describe edges (in XML)	
Path	Description
netconvert/XML2/types/cross_notypes	no types
netconvert/XML2/types/cross_notypes_v	the same, with verbose output
netconvert/XML2/types/cross_usingtypes	with types
netconvert/XML2/types/cross_usingtypes_v	the same, with verbose output
Checks whether description of edge shapes works (in XML)	
Path	Description
netconvert/XML2/shapes/hokkaido-japan	a simple test for the hokkaido-network
Checks whether setting connections and disabling addition of turnaround work	
Path	Description
netconvert/XML2/connections/cross3l_edge2edge_conns	a simple test for setting connections edge-wise
netconvert/XML2/connections/cross3l_lane2lane_conns	a simple test for setting connections lane-wise
netconvert/XML2/connections/cross3l_no_turnarounds	a simple test to check whether appending turnarounds may be disabled
Checks whether error handling works	
Path	Description
netconvert/errors/false_output	Tests what happens if the output can not be written
netconvert/errors/no_output	Tests what happens if no output is given
netconvert/errors/xml_false_edg	Tests what happens if xml-edges can not be read
netconvert/errors/xml_no_edg	Tests what happens if no xml-edges are given
netconvert/errors/xml_false_nod	Tests what happens if xml-nodes can not be read
netconvert/errors/xml_no_nod	Tests what happens if no xml-nodes are given
netconvert/errors/unknown_option	Tests what happens if an unknown option is passed

- Test for `--version` was removed in version 0.9.5

SUMO

Checks whether variable speed signs work	
Path	Description
sumo/extended/ variable_speed_signs/ b0_offset_100	Acceptance Testing using TextTest a scenario with begin time=0, first change at time=100
sumo/extended/ variable_speed_signs/ b100_offset_0	a scenario with begin time=100, first change at time=0
sumo/extended/ variable_speed_signs/ b100_offset_50	a scenario with begin begin time=100, first change at time=50
sumo/extended/ variable_speed_signs/ b100_offset_100	a scenario with begin begin time=100, first change at time=100
sumo/extended/ variable_speed_signs/ b100_offset_200	a scenario with begin time=100, first change at time=200
sumo/extended/ variable_speed_signs/begin_0	a scenario with begin time=0, first change at time=0
Checks whether other emitters work	
Path	Description
sumo/extended/emitter/ 10_time_0_1_start0_0types_1route_noid	ten vehicles, one second between starting at 0, no id, random vehicle type (from 1), one route, no id
sumo/extended/emitter/ 10_time_0_1_start5_0types_1route_noid	ten vehicles, one second between starting at 0, no id, random vehicle type (from 1), one route, no id, sim start at 5 (check whether previous vehicles are discarded)
sumo/extended/emitter/ base_vehtype1from2	as 10_time_0_1_start0_0types_1route_noid, but with a chosen vehicle type
sumo/extended/emitter/ base_vehtype2from2	as 10_time_0_1_start0_0types_1route_noid, but with two randomly chosen vehicle type
sumo/extended/emitter/ base_withid	as 10_time_0_1_start0_0types_1route_noid, but with ids
sumo/extended/emitter/ base_period10	as 10_time_0_1_start0_0types_1route_noid, but with a period of 10s
sumo/extended/emitter/ base_otherroute	as 10_time_0_1_start0_0types_1route_noid, but another route is used
sumo/extended/emitter/ base_2randomroutes	as 10_time_0_1_start0_0types_1route_noid, but a random route is used
sumo/extended/emitter/ base_exp_routes	as 10_time_0_1_start0_0types_1route_noid, with explicit routes
Checks whether other additional structures work	
Path	Description
sumo/extended/rerouter	Tests whether rerouter work; checks also whether vehroutes work properly when vehicles are rerouted
Checks whether error handling works	
Path	Description
sumo/errors/ meandata_edges_missing_begin0	Tests what happens if an unknown option is passed
sumo/errors/ meandata_edges_missing_begin1	Tests what happens if the first begin time is missing
sumo/errors/ meandata_edges_missing_begin2	Tests what happens if the second begin time is missing

- Test for `--version` was removed in version 0.9.5